

View Online at <https://aerobasegroup.com/nsn/5930-01-088-0823>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Driptight and oiltight and watertight

Overall Length:

4.093 inches

Overall Height:

2.000 inches

Overall Width:

1.562 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.187 inches

Actuator Roller Diameter:

0.625 inches

Actuator Roller Width:

0.125 inches

Housing Length:

3.000 inches

Housing Width:

1.562 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.468 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

240.0 ac and 240.0 dc

End Application:

An/msc-67 80053

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

12.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

0.080 pretravel inches and 0.250 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 10.000 amperes resistive ac and 3.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0