NSN 5930-01-088-5612

Electronic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-088-5612 **Overall Length:** 2.060 inches **Overall Height:** 0.675 inches **Overall Width:** 0.836 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +5.0/+33.0 **Vibration Resistance Amplitude:** 6.5 gravitational units **Shock Resistance Rating In Gravitational Units:** 60.0 **Operating Tempurature Range:** +0.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** An-wlq- (v) -80058 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 80.0 megahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:**

Not rated Signal Voltage Rating Per Channel: Not rated **Overall Gain:** Not rated

Impedance Rating Per Channel:

50.000 ohms operating channel

NSN 5930-01-088-5612

Electronic Switch - Page 2 of 2

Fiig: A32200



Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
20.0 milliseconds
Connection Type And Location:
Receptacle, coaxial left side and receptacle, coaxial right side and solder lug right side
Connection Contact Type And Quantity:
3 receptacle, coaxial internal and 4 solder lug external
External Dc Operating Voltage In Volts:
-15.0 2nd voltage err-100
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No