# NSN 5930-01-088-7979

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-088-7979

# Thread Class:

2a single mounting facility

# Thread Length:

0.380 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# Shaft Diameter:

0.250 inches single actuator

# **Overall Diameter:**

1.380 inches

Individual Section Quantity:

1

### End Application:

Loader, scoop 10988

# Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 single section rear

# Throw Quantity:

3 single section rear

# Mounting Method:

Threaded bushing single mounting facility

### **Thread Size:**

0.438 inches single mounting facility

# **Contact Voltage Rating In Volts:**

12.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

3 single actuator

### Shaft Type:

Round single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks, breaks before makes single section rear

### Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

## Style Designator:

Snap or line

# NSN 5930-01-088-7979

Rotary Switch - Page 2 of 2



# **Thread Series Designator:**

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0