

View Online at <https://aerobasegroup.com/nsn/5930-01-088-8323>

Overall Length:

4.281 inches

Overall Height:

2.812 inches

Overall Width:

5.188 inches

Body Length:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+5.00/+75.00 actuation point pounds per square inch gage and +5.00/+75.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0