## NSN 5930-01-088-8325

Toggle Switch - Page 1 of 2

Actuator seal



View Online at https://aerobasegroup.com/nsn/5930-01-088-8325

| Body Style:   |
|---|
| Bushing mount   |
| Hazardous Locations/environmental Protection:                                     |
| Weatherproof  |
| Overall Length:   |
| 0.500 inches  |
| Overall Height:   |
| 1.335 inches  |
| Overall Width:  |
| 0.850 inches  |
| Bushing Length:   |
| 0.354 inches  |
| Body Length:  |
| 0.500 inches  |
| Body Width:   |
| 0.850 inches  |
| Body Height:  |
| 0.475 inches  |
| Case Material:  |
| Plastic   |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.115 inches  |
| Actuator Height:  |
| 0.410 inches  |
| Actuator Position-action Relationship:  |
| Up position momentary and down position maintained and center position maintained |
| Actuator Color:   |
| Natural single actuator   |
| Maximum Voltage Rating In Volts:  |
| 250.0 ac and 28.0 dc  |
| End Application:  |
| F16 air comb fit 81755  |
| Mounting Surface To Terminal End Distance:  |
| 0.571 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Features Provided:  |

## **NSN 5930-01-088-8325** Toggle Switch - Page 2 of 2



| Thready Qty Per Inch (tpi):   |
|---|
| 40  |
| Thread Size:  |
| 0.250 inches  |
| Nonpile-up Contact Arrangement:   |
| 4 pole, double throw, one position momentary, two positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                                     |
| 5.000 amperes resistive dc and 2.000 amperes resistive ac                                 |
| Special Features:   |
| Terminals epoxy sealed  |
| Precious Material And Location:   |
| Contacts and terminal surfaces silver   |
| Thread Series Designator:   |
| Uns   |
| Terminal Type And Quantity:   |
| 12 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A053a0  |
|   |
|   |