

View Online at <https://aerobasegroup.com/nsn/5930-01-088-9604>

Overall Length:

1.822 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.350 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Nonturn Device Radius:

0.375 inches at 4: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 4: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section periphery

Throw Quantity:

7 single section periphery

Mounting Method:

Unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

1 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load highest dc voltage rating at altitude

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0