

View Online at <https://aerobasegroup.com/nsn/5930-01-089-0515>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.750 inches

Overall Height:

2.500 inches

Overall Width:

2.312 inches

First Flat Length:

0.750 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

End Application:

Multi-hull 03950

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Facility Circle Radius:

2.312 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0