

View Online at <https://aerobasegroup.com/nsn/5930-01-089-2186>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.694 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.190 inches

Individual Section Quantity:

9

Nonturn Device Type:

Slotted bushing at 4: 30 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

4920-01-076-3745

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

20 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

63.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

20 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

18.0 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load dc at sea level and 25.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0