

View Online at <https://aerobasegroup.com/nsn/5930-01-089-4212>

Thread Class:

3a single pressure connection

Overall Length:

2.500 inches

Outside Diameter:

0.250 inches single connection

Body Length:

1.550 inches

Overall Diameter:

0.870 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.875 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Inlet connection

Contact Action Stimulus:

Decrease

Proof Pressure:

250.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

400.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point pounds per square inch gage and 16.00 actuation point pounds per square inch gage and 20.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0