NSN 5930-01-090-3193

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-090-3193

Overall Length:
5.281 inches
Overall Height:
2.593 inches
Overall Width:
4.938 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
4.625 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
2000.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
6.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+25.00/+581.00 actuation point pounds per square inch and +27.00/+600.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
6.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

NSN 5930-01-090-3193

Pressure Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0