Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-090-3492

Hazardous Locations/environmental Protection:	
Dustproof	
Overall Length:	
3.260 inches	
Overall Height:	
1.585 inches	
Overall Width:	
1.150 inches	
Unthreaded Mounting Hole Diameter:	
0.100 inches single mounting facility	
Individual Section Quantity:	
4	
Longest Horizontal Distance Between Mounting Centers:	
3.090 inches single mounting facility	
Longest Vertical Distance Between Mounting Centers:	
0.900 inches single mounting facility	
Mounting Method:	
Unthreaded hole single mounting facility	
Actuator Type:	
Thumbwheel all actuators	
Contact Voltage Rating In Volts:	
28.0 dc at sea level	
Mounting Facility Pattern:	
Four position rectangular single mounting facility	
Switch Actuator Indexing Position Quantity:	
16 all actuators	
Terminal Type:	
Printed circuit	
Contact Load Current Rating:	
125.0 milliamperes resistive load dc at sea level	
Readout Indicator Marking:	
0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section	
Contact Arrangement Truth Table:	
Bcd, 1 pole - 16 positions each section	
Special Features:	
0.500 in. Spacer located in station 2	
Color:	
White each indicator marking	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	

Code Indicating Wheel Switch - Page 2 of 2

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

