

View Online at <https://aerobasegroup.com/nsn/5930-01-090-5608>

Thread Length:

0.875 inches single threaded bushing

Hazardous Locations/environmental Protection:

Moisture proof

Overall Height:

10.250 inches

Overall Width:

3.813 inches

Body Height:

6.375 inches

Bulb Length:

2.250 inches

Bulb Diameter:

0.562 inches

End Application:

Adapter assembly 30003

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+350.00 actuation point degrees fahrenheit and +99.00/+347.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Thread Series Designator:

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0