

View Online at <https://aerobasegroup.com/nsn/5930-01-090-5609>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.448 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.750 inches

Individual Section Quantity:

1

End Application:

Namt console 54206

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

15.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+2.500 inch-ounces single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Terminals gold and contact surfaces silver

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0