NSN 5930-01-090-6186

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-090-6186

0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.747 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.560 inches
Actuator Roller Diameter:
0.187 inches
Actuator Roller Width:
0.125 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
7.0 grams
Switch Actuating Force:
40.0 grams
Actuator Movement:
Between 0.085 pretravel inches and 0.018 overtravel inches and 0.019 differential inches

NSN 5930-01-090-6186

Sensitive Switch - Page 2 of 2



Contact	Load Curre	nt Rating	At Maximum	Rated	Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0