# NSN 5930-01-090-6186

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-090-6186

Body St	tyle:
---------	-------

Hole mounted

**Overall Length:** 

0.781 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

#### **Overall Height:**

0.747 inches

#### **Overall Width:**

0.250 inches

**Body Length:** 

#### 0.781 inches

Body Width:

#### 0.250 inches

Body Height:

# 0.356 inches

Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### **Actuator Style:**

Roller arm

#### **Actuator Free Position Height:**

0.560 inches

## Actuator Roller Diameter:

0.187 inches

#### Actuator Roller Width:

0.125 inches

### Maximum Voltage Rating In Volts:

30.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

7.0 grams

## Switch Actuating Force:

40.0 grams

#### **Actuator Movement:**

Between 0.085 pretravel inches and 0.018 overtravel inches and 0.019 differential inches

# NSN 5930-01-090-6186

Sensitive Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

# Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A053a0