NSN 5930-01-090-6753

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-090-6753

Thread Length:
0.500 inches single threaded bushing
Overall Length:
2.000 inches
Body Diameter:
0.250 inches
Body Length:
1.750 inches
Bulb Length:
1.250 inches
Bulb Diameter:
0.250 inches
Tempurature Sensing Element Type:
Bulb
Width Across Flats:
0.620 inches
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
27 single threaded bushing
Contact Action Stimulus:
Increase
Increase Thread Size:
Thread Size:
Thread Size: 0.125 inches single threaded bushing
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 120.00 actuation point degrees fahrenheit and 117.00 deactuation point degrees fahrenheit
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 120.00 actuation point degrees fahrenheit and 117.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 120.00 actuation point degrees fahrenheit and 117.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 120.00 actuation point degrees fahrenheit and 117.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Media For Which Designed:
Thread Size: 0.125 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 5.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 120.00 actuation point degrees fahrenheit and 117.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Media For Which Designed: Gas or liquid

Npt single threaded bushing

NSN 5930-01-090-6753

Thermostatic Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0