

View Online at <https://aerobasegroup.com/nsn/5930-01-090-8015>

Body Style:

Bushing/hole mounted

Overall Length:

2.624 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.859 inches

Overall Width:

0.641 inches

Bushing Length:

0.406 inches

Body Length:

1.812 inches

Body Width:

0.641 inches

Body Height:

1.125 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.145 inches

Actuator Style:

Round

Actuator Diameter:

0.312 inches

Actuator Height:

0.328 inches

Actuator Free Position Height:

0.859 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.218 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0