

NSN 5930-01-090-8015 Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-090-8015 **Body Style:** Bushing/hole mounted **Overall Length:** 2.624 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Height:** 1.859 inches **Overall Width:** 0.641 inches **Bushing Length:** 0.406 inches **Body Length:** 1.812 inches **Body Width:** 0.641 inches **Body Height:** 1.125 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:**

0.145 inches

Actuator Style:

Round

Actuator Diameter:

0.312 inches

Actuator Height:

0.328 inches

Actuator Free Position Height:

0.859 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-090-8015 Sensitive Switch - Page 2 of 2



Switch Release Force:
4.0 ounces
Switch Actuating Force:
30.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.218 overtravel inches and 0.015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Precious Material And Location:
Contacts and terminal surfaces silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0