

View Online at <https://aerobasegroup.com/nsn/5930-01-091-1314>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.660 inches

Overall Height:

4.610 inches

Overall Width:

2.015 inches

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

2.050 inches

Actuator Free Position Height:

2.050 inches

Housing Height:

2.560 inches

Housing Length:

3.660 inches

Housing Width:

2.015 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.750 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

10.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

Between 0.109 pretravel inches and 0.125 overtravel inches and 0.009 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Special Features:

0.500-14 thd conduit opening

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0