

View Online at <https://aerobasegroup.com/nsn/5930-01-091-3318>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.300 inches

Overall Height:

2.035 inches

Bushing Length:

0.500 inches

Body Length:

1.300 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.660 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

S3awst 20551

Mounting Surface To Terminal End Distance:

0.875 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 3.000 amperes motor dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Flexible insulators

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0