

View Online at <https://aerobasegroup.com/nsn/5930-01-091-3318>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.300 inches

**Overall Height:**

2.035 inches

**Bushing Length:**

0.500 inches

**Body Length:**

1.300 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.660 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

S3awst 20551

**Mounting Surface To Terminal End Distance:**

0.875 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 3.000 amperes motor dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Flexible insulators

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0