

View Online at <https://aerobasegroup.com/nsn/5930-01-091-3787>

Hazardous Locations/environmental Protection:

Vibration proof

Overall Length:

Between 3.865 inches and 3.885 inches

Body Length:

1.905 inches

Overall Diameter:

Between 0.970 inches and 1.030 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.980 inches and 1.000 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+400.00/+3000.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point hex nut

Contact Voltage Rating In Volts:

28.0 dc at altitude single voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0