## NSN 5930-01-091-3964

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-091-3964

Inside Diameter:
0.125 inches single connection
Overall Length:
1.438 inches
Overall Height:
3.203 inches
Overall Width:
1.438 inches
Body Height:
2.688 inches
Unthreaded Mounting Hole Diameter:
0.201 inches
Distance Between Mounting Facility Centers:
0.625 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+250.00/+910.00 actuation point pounds per square inch and +280.00/+1000.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

## **NSN 5930-01-091-3964**Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0