NSN 5930-01-091-3965

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-091-3965

| Overall Length: |
|-----------------|
| 4.750 inches |
| Overall Height: |

6.230 inches

Overall Width:

3.100 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

6.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+350.00/+750.00 actuation point pounds per square inch and +300.00/+700.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Stimulus Rating:

50.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

NSN 5930-01-091-3965

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0