# NSN 5930-01-091-5557

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-091-5557

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

3.669 inches

#### **Overall Height:**

1.469 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

1.875 inches single actuator

#### **Nonturn Device Radius:**

## 0.437 inches at 9:00 o'clock

### Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 single section front

#### **Throw Quantity:**

6 single section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

12 single actuator

## Shaft Type:

Round single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-01-091-5557

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Adjustable stop single actuator

#### **Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

## Precious Material And Location:

Contact surfaces silver

# **Precious Material:**

Silver

## Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A052b0