

View Online at <https://aerobasegroup.com/nsn/5930-01-091-9184>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Length:**

2.812 inches

**Overall Height:**

5.469 inches

**Overall Width:**

4.875 inches

**Body Height:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

216.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, double break, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

7.4 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+10.00/+180.00 actuation point pounds per square inch gage and +10.00/+180.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Voltage Rating In Volts:**

115.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0