NSN 5930-01-091-9196

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-01-091-9196

Watertight
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.370 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.790 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.120 inches
Actuator Free Position Height:
0.700 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
4.0 inch-ounces
Switch Actuating Force:
Between 16.0 ounces and 26.0 ounces
Actuator Movement:
Between 0.090 pretravel inches and 0.005 overtravel inches and 0.030 differential inches

NSN 5930-01-091-9196

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Terminal Type And Quantity:

_		
h	CCI	ew

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0