NSN 5930-01-092-0286

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-092-0286

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

1.315 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.440 inches single actuator

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3: 00 o'clock

End Application:

Forrestal class cv

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-01-092-0286

Rotary Switch - Page 2 of 2



Contact Load Current Rating

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Clips silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0