

View Online at <https://aerobasegroup.com/nsn/5930-01-092-1436>

Thread Class:

2a 1st mounting facility

Thread Length:

0.312 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

3.875 inches

First Flat Length:

0.280 inches 1st actuator

Flat Height:

0.216 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.000 inches 2nd actuator

Overall Diameter:

1.188 inches

Unthreaded Mounting Hole Diameter:

0.136 inches 2nd mounting facility

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

1.718 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section front

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

5 1st actuator

Shaft Type:

Round, hollowed, flatted 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Detent Rotational Torque Range:

+2.000/+13.000 inch-ounces 2nd actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material:

Gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0