NSN 5930-01-092-2584

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-092-2584

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.875 inches
Body Width:
0.344 inches
Body Height:
0.594 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.078 inches
Actuator Free Position Height:
0.475 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 grams
Switch Actuating Force:
17.0 grams
Actuator Movement:
Between 0.050 pretravel inches and 0.004 overtravel inches and 0.050 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
2.500 amperes inductive dc and 4.000 amperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
No.

No

NSN 5930-01-092-2584

Sensitive Switch - Page 2 of 2



Fiig:

A053a0