

View Online at <https://aerobasegroup.com/nsn/5930-01-092-2981>

**Body Style:**

Bushing mount

**Overall Length:**

0.500 inches

**Overall Height:**

0.889 inches

**Overall Width:**

0.275 inches

**Bushing Length:**

Between 0.282 inches and 0.296 inches

**Body Length:**

0.500 inches

**Body Width:**

0.275 inches

**Body Height:**

0.350 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.840 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

20.0 ac and 20.0 dc

**Mounting Surface To Terminal End Distance:**

0.600 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 2.000 amperes resistive ac

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0