

View Online at <https://aerobasegroup.com/nsn/5930-01-092-3786>

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.312 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A052b0