

View Online at <https://aerobasegroup.com/nsn/5930-01-092-7498>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

1.690 inches

**Body Diameter:**

0.330 inches

**Bushing Length:**

0.370 inches

**Body Length:**

0.880 inches

**Overall Diameter:**

0.330 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.170 inches

**Actuator Height:**

0.190 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Full display lens

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac and 3.000 amperes resistive dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0