## NSN 5930-01-092-9092

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-092-9092

Body Style:
Hole mounted
Overall Length:
0.789 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.790 inches
Overall Width:
0.250 inches
Body Length:
0.789 inches
Body Width:
0.250 inches
Body Height:
0.510 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.296 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.330 inches
Maximum Voltage Rating In Volts:
115.0 ac
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches
Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5930-01-092-9092

Sensitive Switch - Page 2 of 2



Terminal Type And Quantit	у:
---------------------------	----

3 tab, solder lug

**Specification Data:** 

96906-ms27216 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0