NSN 5930-01-092-9121

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-092-9121

Body Style:
Hole mounted
Overall Length:
4.000 inches
Overall Height:
3.640 inches
Overall Width:
1.500 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.640 inches
Actuator Roller Diameter:
0.050 inches
Actuator Roller Width:
0.157 inches
Housing Height:
2.000 inches
Housing Length:
4.000 inches
Housing Width:
1.500 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
Between 1.595 inches and 1.655 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Between 3.240 inches and 3.260 inches
Maximum Voltage Rating In Volts:
230.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
40.0 ounces
Actuator Movement:
Between 0.125 pretravel inches and 0.125 overtravel inches and 0.060 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

NSN 5930-01-092-9121

Sensitive Switch - Page 2 of 2



Special	Features:
---------	-----------

Altered iaw hughes aircraft dwg no. 1656582

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0