

View Online at <https://aerobasegroup.com/nsn/5930-01-092-9771>

Body Style:

Printed circuit

Hazardous Locations/environmental Protection:

Dustproof and vibration resistant and shock resistant

Overall Length:

Between 0.870 inches and 0.890 inches

Overall Height:

Between 0.578 inches and 0.628 inches

Overall Width:

Between 0.370 inches and 0.390 inches

Body Length:

Between 0.870 inches and 0.890 inches

Body Width:

Between 0.370 inches and 0.390 inches

Body Height:

Between 0.237 inches and 0.257 inches

Case Material:

Plastic

Switch Actuator Quantity:

8

Actuator Style:

Rectangular

Actuator Height:

Between 0.195 inches and 0.205 inches

Actuator Width:

0.070 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

8 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes resistive dc

Precious Material And Location:

Contact surfaces gold

Test Data Document:

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 printed circuit

Specification Data:

81349-mil-s-83504/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0