

View Online at <https://aerobasegroup.com/nsn/5930-01-093-0334>

Overall Length:

3.813 inches

Body Diameter:

4.250 inches

Overall Diameter:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.125 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.625 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+250.00 actuation point degrees fahrenheit and +50.00/+250.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

24.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0