

View Online at <https://aerobasegroup.com/nsn/5930-01-093-0816>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight and corrosion resistant

**Overall Length:**

4.660 inches

**Overall Height:**

1.780 inches

**Overall Width:**

1.650 inches

**Case Material:**

Metal

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.820 inches

**Actuator Roller Diameter:**

0.440 inches

**Housing Height:**

1.780 inches

**Housing Length:**

2.840 inches

**Housing Width:**

1.650 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.560 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.342 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 230.0 dc

**End Application:**

Louver metal 96169

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

96.0 ounces

**Actuator Movement:**

0.040 pretravel inches and 0.280 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

50.000 milliamperes resistive dc and 750.000 milliamperes resistive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0