

View Online at <https://aerobasegroup.com/nsn/5930-01-093-0816>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Overall Length:

4.660 inches

Overall Height:

1.780 inches

Overall Width:

1.650 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.820 inches

Actuator Roller Diameter:

0.440 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.560 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.342 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

End Application:

Louver metal 96169

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.280 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 750.000 milliamperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0