

View Online at <https://aerobasegroup.com/nsn/5930-01-093-2547>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.675 inches

Overall Height:

2.450 inches

Overall Width:

1.050 inches

Body Diameter:

1.000 inches

Bushing Length:

0.465 inches

Body Length:

1.000 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

6l16b oxygen 14122

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

1.000 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0