# NSN 5930-01-093-4224

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-093-4224

Overall Length:

5.188 inches

**Overall Width:** 

2.812 inches

Body Height:

2.750 inches

**Unthreaded Mounting Hole Diameter:** 

0.281 inches

Capillary Tube Length:

120.0 inches

Bulb Length:

9.000 inches

**Bulb Diameter:** 

0.688 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and unthreaded hole

#### **Features Provided:**

Electrical access port

**Contact Action Stimulus:** 

Increase

Mounting Facility Pattern:

Isosceles triangle

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+130.00 actuation point degrees fahrenheit and +60.00/+130.00 deactuation point degrees fahrenheit

## Contact Adjustment Type:

External deactuation point screw and external actuation point screw

## NSN 5930-01-093-4224

Thermostatic Switch - Page 2 of 2



**Contact Voltage Rating In Volts:** 

550.0 dc at sea level third voltage

## Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0