# NSN 5930-01-093-6416

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-093-6416

# Thread Class:

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## **Overall Length:**

1.563 inches

## Shaft Diameter:

0.125 inches single actuator

#### Shaft Length:

0.750 inches single actuator

## **Overall Diameter:**

0.500 inches

## Individual Section Quantity:

1

## Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 single section rear

#### Throw Quantity:

2 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Makes before breaks single section rear

#### Switch Actuator Positioning Increment:

36.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

50.0 milliamperes resistive load ac at sea level

# NSN 5930-01-093-6416

Rotary Switch - Page 2 of 2



**Precious Material And Location:** 

Terminal surfaces gold and contacts and terminals silver

#### **Precious Material:**

Gold and silver

Style Designator:

Snap or line

# Thread Series Designator:

Unf single mounting facility

## Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A052b0