

View Online at <https://aerobasegroup.com/nsn/5930-01-093-6419>

Body Style:

Hole mounted

Overall Length:

1.515 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Width:

0.400 inches

Body Length:

1.109 inches

Body Width:

0.400 inches

Body Height:

0.640 inches

Unthreaded Mounting Hole Diameter:

0.126 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.109 inches

Actuator Width:

0.187 inches

Actuator Free Position Height:

0.625 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0