NSN 5930-01-093-6419



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-093-6419 **Body Style:** Hole mounted **Overall Length:** 1.515 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Width:** 0.400 inches **Body Length:** 1.109 inches **Body Width:** 0.400 inches **Body Height:** 0.640 inches **Unthreaded Mounting Hole Diameter:** 0.126 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.406 inches **Actuator Length:** 0.110 inches **Actuator Style:** Rectangular **Actuator Height:** 0.109 inches **Actuator Width:** 0.187 inches **Actuator Free Position Height:** 0.625 inches **Actuator Adapter Style:** Roller leaf **Maximum Voltage Rating In Volts:** 125.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

6.0 ounces

NSN 5930-01-093-6419

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0