

View Online at <https://aerobasegroup.com/nsn/5930-01-093-8546>

Inside Diameter:

0.156 inches all connections

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.000 inches

Outside Diameter:

0.188 inches all connections

Overall Height:

1.000 inches

Overall Width:

0.423 inches

Body Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.086 inches

Longest Horizontal Distance Between Mounting Centers:

0.719 inches

Longest Vertical Distance Between Mounting Centers:

0.719 inches

End Application:

427mmtncmplex8 11530

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 40.0 degrees fahrenheit and 150.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

15.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

10.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

10.50 actuation point inches of water and 10.00 deactuation point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Media For Which Designed:

Gas

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0