

View Online at <https://aerobasegroup.com/nsn/5930-01-093-8547>

Hazardous Locations/environmental Protection:

Dustproof

Length:

Between 1.240 inches and 1.260 inches

Overall Height:

Between 0.567 inches and 0.605 inches

Body Diameter:

0.640 centimeters

Body Height:

Between 0.357 inches and 0.395 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 500.0 milliamperes lamp load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

40.00 actuation point degrees fahrenheit and 35.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at altitude third voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0