

View Online at <https://aerobasegroup.com/nsn/5930-01-093-9514>

Inside Diameter:

0.250 inches single connection

Overall Length:

7.062 inches

Overall Height:

2.500 inches

Overall Width:

4.375 inches

Mounting Slot Width:

0.343 inches

Body Length:

5.250 inches

Distance Between Mounting Facility Centers:

5.875 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

24000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+600.00/+17450.00 actuation point pounds per square inch and +1150.00/+18000.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0