

View Online at <https://aerobasegroup.com/nsn/5930-01-094-1434>

Overall Length:

Between 1.190 inches and 1.260 inches

Overall Height:

Between 0.468 inches and 0.613 inches

Body Diameter:

Between 0.560 inches and 0.640 inches

Mounting Slot Width:

0.140 inches

Body Height:

Between 0.295 inches and 0.325 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Mounting Facility Centers:

0.937 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Slot and unthreaded hole

Features Provided:

Hermetically sealed case

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage and 1.0 amperes lamp load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

115.00 actuation point degrees fahrenheit and 85.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-s-24236 spec.