NSN 5930-01-094-5855

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-094-5855

| Body Style: | | | |
|---|--|--|--|
| Hole mounted | | | |
| Hazardous Locations/environmental Protection: | | | |
| Dustproof | | | |
| Overall Length: | | | |
| 1.375 inches | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | |
| 0.875 inches | | | |
| Overall Height: | | | |
| 0.875 inches | | | |
| Overall Width: | | | |
| 0.406 inches | | | |
| Body Length: | | | |
| 1.094 inches | | | |
| Body Width: | | | |
| 0.406 inches | | | |
| Body Height: | | | |
| 0.625 inches | | | |
| Case Material: | | | |
| Plastic | | | |
| Unthreaded Mounting Hole Diameter: | | | |
| 0.130 inches | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | | | |
| 0.406 inches | | | |
| Actuator Length: | | | |
| 0.110 inches | | | |
| Actuator Style: | | | |
| Rectangular | | | |
| Actuator Width: | | | |
| 0.165 inches | | | |
| Actuator Free Position Height: | | | |
| 0.578 inches | | | |
| Maximum Voltage Rating In Volts: | | | |
| 277.0 ac and 250.0 dc | | | |
| End Application: | | | |
| Multi-hull 03950 | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Nonpile-up Contact Arrangement: | | | |
| 1 pole, double throw, one position momentary single switch unit | | | |

4.0 ounces

Switch Release Force:

NSN 5930-01-094-5855

Sensitive Switch - Page 2 of 2



| Switch Actuating Force | Switch | Actuating | Force: |
|------------------------|--------|------------------|--------|
|------------------------|--------|------------------|--------|

Between 6.0 ounces and 14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 11.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0