

View Online at <https://aerobasegroup.com/nsn/5930-01-094-5855>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.406 inches

**Body Length:**

1.094 inches

**Body Width:**

0.406 inches

**Body Height:**

0.625 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.578 inches

**Maximum Voltage Rating In Volts:**

277.0 ac and 250.0 dc

**End Application:**

Multi-hull 03950

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 11.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0